



SAE AADL: An Industry Standard for Embedded Systems Engineering

Peter Feiler

Software Engineering Institute

phf@sei.cmu.edu

412-268-7790



Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 01 FEB 2005		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE SAE AADL: An Industry Standard for Embedded Systems Engineering				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Carnegie Mellon University Software Engineering Institute				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES See also ADM00001742, HPEC-7 Volume 1, Proceedings of the Eighth Annual High Performance Embedded Computing (HPEC) Workshops, 28-30 September 2004 Volume 1., The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 25	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

SAE AADL Standard

An Enabler of Predictable Model-Based System Engineering

- Notation for specification of task and communication architectures of Real-time, Embedded, Fault-tolerant, Secure, Safety-critical, Software-intensive systems
- Fields of application: Avionics, Automotive, Aerospace, Autonomous systems, ...
- Based on 15 Years of DARPA funded technologies
- Standard approved by SAE in Sept 2004
- www.aadl.info





SAE AS-2C AADL Subcommittee

- Bruce Lewis (US Army AMRDEC): Chair
- Peter Feiler (SEI): technical lead, author & editor
- Steve Vestal (Honeywell): co-author
- Ed Colbert (USC): UML Profile of AADL
- Joyce Tokar (Pyrrhus Software): Ada & C Annex

Other Voting Members

- Boeing, Rockwell, Honeywell, Lockheed Martin, Raytheon, Smith Industries, General Dynamics, Airbus, Axlog, European Space Agency, TNI, Dassault, EADS, High Integrity Solutions

Coordination with

- NATO Aviation, NATO Plug and Play, French Government COTRE, SAE AS-1 Weapons Plug and Play, OMG UML & SysML



Potential Users

- Airbus
- European Space Agency
- Rockwell Collins
- Lockheed Martin
- Smith Industries
- Raytheon
- Boeing FCS
- Common Missile
- System Plug and Play

**New System Engineering Approach
incorporates AADL**

**Modeling of Satellite
Systems, Architecture
Verification - ASSERT**

**Modeling of Avionics
Computer System**

**Embedded System
Engineering & AADL**

**Apply AADL for systems
integration modeling & analysis**

**NATO/SAE AS1 Weapon
System Integration**

AADL-Based Engineering

System Analysis

- Schedulability
- Performance
- Reliability
- Fault Tolerance
- Dynamic Configurability

System Integration

- Runtime System Generation
- Application Composition
- System Configuration

Software
System
Engineer

Architecture
Modeling
Abstract, but
Precise

SAE AADL

Predictive
Embedded
System
Engineering
Reduced
Development &
Operational Cost

Application
Software

Execution
Platform

Composable
Components


GPS	DB	HTTPS	Ada Runtime
-----	----	-------	-------------

.....

Devices	Memory	Bus	Processor
---------	--------	-----	-----------



A Partitioned Portable Architecture



Strong Partitioning

- Timing Protection
- OS Call Restrictions
- Memory Protection

Interoperability/Portability

- Tailored Runtime Executive
- Standard RTOS API
- Application Components



MetaH: Proof of Concepts for AADL

- 1991 DARPA DSSA program begins
- 1992 Partitioned PFP target (Tartan MAR/i960MC)
- 1994 Multi-processor target (VME i960MC)
- 1995 Slack stealing scheduler
- 1998 Portable Ada 95 and POSIX middleware configurations
- 1998 Extensibility through MetaH-ACME Mapping
- 1998 Reliability modeling extension
- 1999 Hybrid automata verification of core middleware modules

Numerous evaluation and demonstration projects, e.g.

- Missile G&C reference architecture, demos, others (AMCOM SED)
- Hybrid automata formal verification (AFOSR, Honeywell)
- Missile defense (Boeing)
- Fighter guidance SW fault tolerance (DARPA, CMU, Lockheed-Martin)
- Incremental Upgrade of Legacy Systems (AFRL, Boeing, Honeywell)
- Comanche study (AMCOM, Comanche PO, Boeing, Honeywell)
- Tactical Mobile Robotics (DARPA, Honeywell, Georgia Tech)
- Advanced Intercept Technology CWE (BMDO, MaxTech)
- Adaptive Computer Systems (DARPA, Honeywell)
- Avionics System Performance Management (AFRL, Honeywell)
- Ada Software Integrated Development/Verification (AFRL, Honeywell)
- FMS reference architecture (Honeywell)
- JSF vehicle control (Honeywell)
- IFMU reengineering (Honeywell)



AADL in Context

Research ADLs

- MetaH
 - Real-time, modal, system family
 - Analysis & generation
 - RMA based scheduling
- Rapide, Wright, ..
 - Behavioral validation
- ADL Interchange
 - ACME

**DARPA Funded
Research since 1990**

Basis

Extension

Influence

UML Profile

Alignment

Enhancement

AADL
Extensible
Real-time
Dependable

Industrial Strength

- UML 2.0, UML-RT
- HOOD/STOOD
- SDL

Airbus & ESA

AADL: The Language

Components with precise semantics

- Thread, thread group, process, system, processor, device, memory, bus, data, subprogram

Completely defined interfaces & interactions

- Data & event flow, synchronous call/return, shared access
- End-to-End flow specifications

Real-time Task Scheduling

- Supports different scheduling protocols incl. GRMA, EDF
- Defines scheduling properties and execution semantics

Modal, configurable systems

- Modes to model transition between statically known states & configurations

Component evolution & large scale development support


AADL language extensibility






Thread Execution Semantics

- Dispatch protocols
- Nominal & recovery
- Fault handling
- Resource locking
- Mode switching
- Initialization & finalization





Execution Platform Bindings






An Avionics System Case Study

- Migration from static timeline to preemptive scheduling
 - Identified issues with shared variable communication
 - Migration potential from polling tasks to event-driven tasks
- Flexibility, predictability & efficiency of port-based communication
 - Defined communication timing semantics
 - Support for deterministic transfer & optimized buffers
- Effectiveness of connection & flow semantics
 - Support end-to-end latency analysis
- Analyzable fault-tolerant redundancy patterns
 - Orthogonal architecture view without model clutter






A Naïve Thread-based Design



Decreasing Priority



Flight Manager in AADL



Data Stream Latency Analysis

- Flow specifications in AADL
 - Properties on flows: expected & actual end-to-end latency
 - Properties on ports: expected incoming & estimated output latency
- End-to-end latency contributors
 - Delayed connections result in sampling latency
 - Immediate periodic & aperiodic sequences result in cumulative execution time latency
- Phase delay shift & oscillation
 - Noticeable at flow merge points
 - Variation interpreted as noisy signal to controller

Potential hazard

Latency calculation &
jitter accumulation



Other Flow Characteristics


- Miss rate of data stream
 - Accommodates incomplete sensor readings
 - Allows for controlled deadline misses
- State vs. state delta communication
 - Data reduction technique
 - Implies requirement for guaranteed delivery
- Data accuracy
 - Reading accuracy
 - Computational error accumulation
- Message acknowledgment semantics
 - In terms of flow steps







Redundancy Specification

- Redundancy abstraction
- Co-location constraints on execution platform binding





Primary/Backup Patterns


Passive Backup




Hot Standby



Continuous State Exchange




Voted Output



Primary Backup Synchronization

- External and internal mode control
- Errors reported as events
- Supports reasoning about Primary/Backup logic





AADL Language Extensions

- New properties through property sets
- Sublanguage extension
 - Annex subclauses expressed in an annex-specific sublanguage
- Project-specific language extensions
- Language extensions as approved SAE AADL standard annexes
- Examples
 - Reliability modeling
 - ARINC 653
 - Behavior
 - Constraint sublanguage





Example Annex Extension

```
THREAD t
FEATURES
  sem1 : DATA ACCESS semaphore;
  sem2 : DATA ACCESS semaphore;
END t;
```

THREAD IMPLEMENTATION t.t1

PROPERTIES

Period => 13.96ms;

cotre::Priority => 1;

cotre::Phase => 0.0ms;

Dispatch_Protocol => Periodic;

COTRE thread
properties

```
ANNEX cotre.behavior {**
```

STATES

s0, s1, s2, s3, s4, s5, s6, s7, s8 : **STATE**;

s0 : **INITIAL STATE**;

TRANSITIONS

s0 -[]-> s1 { **PERIODIC_WAIT** };

s1 -[]-> s2 { **COMPUTATION**(1.9ms, 1.9ms) };

s2 -[sem1.wait ! (-1.0ms)]-> s3;

s3 -[]-> s4 { **COMPUTATION**(0.1ms, 0.1ms) };

s4 -[sem2.wait ! (-1.0ms)]-> s5;

s5 -[]-> s6 { **COMPUTATION**(2.5ms, 2.5ms) };

s6 -[sem2.release !]-> s7;

s7 -[]-> s8 { **COMPUTATION**(1.5ms, 1.5ms) };

s8 -[sem1.release !]-> s0;

**);

END t.t1;

COTRE behavioral annex

Courtesy of





Reliability Modeling Approach


Error state & occurrence model as AADL extension

- Error states and transitions
- Fault events & occurrence rates
- Error propagation rates
- Masking of subcomponent and propagation errors

**Reflects hazard analysis,
component failure modes &
effects analysis**


Architecture model provides

- Dependency information
- Isolation analysis
- Basis for stochastic process model generation





An XML-Based AADL Tool Strategy



Open Source AADL Tool Environment

- OSATE is
 - Developed by the Software Engineering Institute
 - Available at under a no cost Common Public License (CPL)
 - Implemented on top of Eclipse Release 3 (www.eclipse.org)
 - Generated from an AADL meta model using the Eclipse Modeling Framework (EMF)
 - A textual & graphical AADL front-end with semantic & XML/XMI support
 - Extensible through architecture analysis & generation plug-ins
- OSATE offers
 - Low cost entrypoint to the use of SAE AADL



SAE AADL and OSATE: Enablers of Embedded Systems Research

- Industry standard architecture modeling notation & model interchange format facilitates
 - Interchange of architecture models between contractors & subcontractors
 - Common architecture model for non-functional system property analysis from different perspectives
 - In-house prototyping of project specific architecture analysis & generation
 - Architecture research with access to industrial models & industry exposure to research results

